



21401 Hemlock Ave. Lakeville, MN 55044  
 Phone: 952-469-4130 [www.vi-king.com](http://www.vi-king.com) Fax: 952-469-4132

**Congratulations on your purchase of Viking Warrior™ double adjustable shock absorbers! You can rest assured that you are getting the best value for your dollar with Viking high performance shocks.**

**INSTALLATION / TUNING GUIDE FOR  
 VIKING WARRIOR DOUBLE ADJUSTABLE  
 CUSTOM MOUNT (EYE / EYE) SHOCKS  
 [Part Numbers D201 – D2xx]**

Each Viking Warrior™ double adjustable custom mount shock includes:

PART NUMBER	QUANTITY	DESCRIPTION
D2xx	1	DOUBLE ADJUSTABLE SHOCK
<i>BEARING MOUNT SHOCKS ONLY:</i> SSBxxT-APK	1	INCLUDES (2) BEARINGS, (4) SNAP RINGS
<i>POLY MOUNT SHOCKS ONLY:</i> 9556-104	2	1/2" SLEEVES
9556-105	2	5/8" SLEEVES

It is important to note that your **shocks should never be used as a travel limiter**. Straps or cables made for travel limitation should be used prevent topping out. Vehicles used in a manner where they could bottom out the shocks (such as drag racing) should use a higher rate spring and a bump stop to help prevent shock damage. Any shock can be damaged from wheel stands despite bump stops. The installation of the shock is recommended at the following ride heights in order to avoid having the shock possibly top or bottom out, which could cause damage to the shock that is not covered by warranty.

SHOCK PART NUMBER	RECOMMENDED RIDE HEIGHT	SHOCK STROKE
D201, D201-W, D202	9 5/8" – 10 1/4"	2.44"
D203, D203-W, D204	10 3/4" – 11 5/8"	3.19"
D205, D205-W, D206	11 5/8" – 12 5/8"	3.82"
D217, D217-W, D218	12 3/8" – 13 3/8"	4.57"
D207, D207-W, D208	13 1/4" – 14 1/4"	5.25"
D209, D209-W, D210	13 7/8" – 15 1/8"	5.75"
D211, D211-W, D212	15 1/8" – 16 1/2"	6.07"
D213, D213-W, D214	15 5/8" – 17 1/8"	6.59"
D219, D219-W, D220	16 5/8" – 18 3/8"	7.42"
D215, D215-W, D216	18 3/8" – 20 1/4"	8.69"

**Longer stroke shocks now available. Please call to inquire!**

## INSTALLATION

**Please read these instructions carefully and entirely prior to installing your new Viking shocks.**

1. Verify that your shocks are the correct lengths and mount style before beginning installation. Contact your chassis builder, supplier or Viking if you have any questions.
2. Measure your vehicle's ride height by measuring from the center point of the fender lip down to the ground. Mark the spot you measured to for later reference.
3. Reference your vehicle's owner's manual to determine the proper jacking locations, and the instructions for removing the shocks and springs. **FAILURE TO FOLLOW THE INSTRUCTIONS CAN RESULT IN SERIOUS INJURY OR DEATH.**
4. Jack your vehicle up until the tires do not touch the ground and the suspension hangs freely and remove the wheels. Remove the shocks and retain all mounting hardware.
5. Fully extend the piston rod and ensure that the jam nut under the bearing housing is secure.
6. Insert the proper poly sleeves or bearing mounts into the shock ends. For bearing mount shocks, insert the bearing in a twisting motion. It may be necessary to press the bearings into the shock. If so, do **not** press on the ball; press only on the race surrounding the ball. Install snap rings on both sides of each bearing and ensure they are fully seated in the loops.
7. Install the shock on the vehicle.
8. Reattach the wheels and torque everything to the specifications defined by the vehicle's manufacturer.
9. Verify that there is clearance around the shock and that the suspension does not bind at all, even when wheels are turned to full lock position.
10. Remove the jack stands and carefully place the car on the ground to check clearances again. Lightly bounce the vehicle at each corner to verify that there are not any clearance issues.
11. Measure the ride height as you did prior to installation and ensure that there is sufficient travel in both directions. Ideally, 60% of the shock stroke is available for compression. **INCORRECT RIDE HEIGHT COULD RESULT IN DAMAGE TO THE SHOCK THAT IS NOT COVERED UNDER WARRANTY.**

## TUNING AND ADJUSTMENT INSTRUCTIONS

Vehicles used on the street, drag cars, and road racers will all have different needs in terms of shock valving. However, it does not stop there. Driver style / capability, road / track conditions, vehicle type (car vs. pickup, etc.), vehicle weight, horsepower, tires, etc. all create different needs in terms of shock valving. That is the beauty of a double adjustable shock. Your Viking shocks have a total of 19 positions (18 clicks plus a zero position) of adjustment per knob, for a total of 361 different valvings. Compression and rebound are independently controlled on the Viking shocks. The "C" knob adjusts compression, while the "R" knob adjusts rebound. Every Viking shock is tested on a dynamometer prior to shipment to ensure that it is functioning properly. Manually moving a shock is not an accurate testing method for ensuring that shocks are functioning properly. Position zero is the softest setting and is found by turning the knob counterclockwise until the positive stop is located. Position 18 is the stiffest setting. Only very light force is needed to adjust the knobs; do not ever force the knob past its intended stop as doing so will damage the shock.

Recommended baseline points for adjusting your Viking shocks are as follows:

Ride Quality/Street:      Front: 1 - 4 compression; 4 - 8 rebound  
    Rear: 0 - 3 compression; 2 - 5 rebound

In general, for good handling and excellent ride quality, the rebound should be set roughly 2 to 6 clicks higher than the compression. For example, a good starting point for the street is 2 clicks on compression and 6 clicks on rebound on the front and 1 click on compression and 3 clicks on rebound on the rear.

Handling:                      Front: 8 - 10 compression; 10 - 14 rebound  
    Rear: 6 - 8 compression; 8 - 12 rebound

Autocross:                     Front: 10 - 14 compression; 14 - 18 rebound  
    Rear: 6 - 10 compression; 10 - 14 rebound

The handling and autocross settings will vary depending on spring rate. If extra firm springs are utilized, the compression setting might be set softer and the rebound setting firmer.

Drag Racing:                 Front: 12 - 18 compression; 0 - 4 rebound  
 (<600 HP)                     Rear: 0 - 4 compression; 4 - 10 rebound

Drag Racing:                 Front: 12 - 18 compression; 0 - 6 rebound  
 (600-900 HP)                 Rear: 2 - 6 compression; 6 - 12 rebound

Drag Racing:                 Front: 12 - 18 compression; 2 - 8 rebound  
 (>900 HP)                     Rear: 2 - 6 compression; 12 - 18 rebound

**Note: Viking Crusader high force rebound rear shocks are strongly recommended for any vehicle with over 750 HP, especially small tire/drag radial vehicles.**

For drag racing, the racer needs to understand how he wants the car to react. Based on all the factors already mentioned, does the racer want to maximize weight transfer? If so, the front will be set with a stiffer compression and soft rebound, while the rear will have a soft compression and stiffer rebound. If the racer desires to limit weight transfer, the setting will go in the opposite direction.



## OTHER PRODUCTS FROM VIKING

### **Coil-Over Springs**

**Made in the U.S.A.** Ultra-lightweight, high travel springs provide up to a 25% weight savings over some other springs in the market! Lifetime guaranteed to remain within 2% of the original free height and rate

### **Rod End & Spherical Bearings, Adjusters, Clevises, Solid Rod Eyes, Jam Nuts**

- Huge selection of styles, materials and sizes
  - o Sizes 3/16" – 1" stocked as standard, larger sizes available upon request
  - o Aluminum and stainless, chromoly and carbon steel bearings stocked as standard
  - o Injection molded loaded slot and two-piece stocked as standard; other styles available special order
- 2 year materials and workmanship warranty

### **New Products**

- Follow Viking on Facebook at: [www.facebook.com/vikingperformance](http://www.facebook.com/vikingperformance) to get the most up-to-date product releases first!

## WARRANTY

Viking warrants that the products will be free from defects in material and workmanship for two years from date of sale to the original purchaser. Viking makes no other warranty of any kind, express or implied. Viking shall have no obligation under the foregoing warranty where the defect is the result of improper or abnormal use, your negligence, vehicle accident, improper or incorrect installation or maintenance, nor when the product has been repaired or altered in any way. Viking's liability in the case of defective products subject to the foregoing warranty shall be limited to the repair or replacement only, at Viking's option, of the defective products. In no event shall Viking be liable for the cost of procurement of substitute products, or liable for any indirect, special, incidental, consequential or exemplary damages for any reason. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

In order to be eligible for service under this warranty, return the defective part to Viking together with the pre-approved R.G.A. number issued by Viking. Tag each item with the part number and the specific explanation of defect. All returns must be shipped prepaid to: Viking Performance, Inc., RGA # \_\_\_\_\_, 21401 Hemlock Ave., Lakeville, MN 55044.

Purchaser acknowledges that parts and services sold by Viking are exposed to a wide variety of conditions, and that Viking does not have full knowledge of the intended use of the goods. Purchaser agrees to indemnify and hold Viking harmless upon demand against all claims, actions, loss, damage or injury resulting from the direct or indirect use of the products, or purchaser's inability to determine the proper use or application of the products. Viking shall not be liable for any claims, demands, injuries, damages, actions, or causes of action whatsoever to buyer arising out of or connected with the use of any Viking products. MOTORSPORTS ARE DANGEROUS; AS SUCH, NO WARRANTY OR REPRESENTATION IS MADE AS TO THE PRODUCTS' ABILITY TO PROTECT THE USER FROM INJURY OR DEATH. THE USER FULLY ASSUMES THAT RISK. ALL PRODUCTS ARE INTENDED FOR RACING AND OFF-ROAD USE AND MAY NOT BE LEGALLY USED ON THE HIGHWAY. We reserve the right to change specifications without notice.